



EKINOX dual screen is a screen stand for both display and videoconferencing. The stand can accommodate two 40" to 55" screens and 60" to 65" Led.

CHARACTERISTICS

- Stainless steel base with standard black mat finish
- Brushed stainless steel column with interior wiring duct (1700 x 170 x 60 mm)
- Standard heavy load rollers, 35 mm diameter (already mounted)
- Screen mount height ranging from 1300 mm to 1700 mm from floor level, in 50mm increments
- Rear casing in black satin Plexiglas™
- Dimensions (w x d x h) :
1800 x 650 x 1750 mm (40"/46")
2130 x 650 x 1750 mm (50"/55")
2130 x 650 x 1750 mm (60"/65")
- Dual universal screen bar Vesa 800 x 400 mm
- Maximum total two screens weight:
90 kg for 40/55" and 30 kg for 60/65"
- Weight: 85 Kg

OPTIONS

- Compact shelf for peripherals and cameras, compatible with all brands, with surface area: 300 mm (w) x 230 mm (d) - Ref: AX0011
- Large shelf for peripherals or Codecs with surface area: 450 mm (w) x 300 mm (d) - Ref: AX0012
- Universal camera stand compatible with all leading manufacturers - Ref: Scuv3
- Scuv3 option: Adaptor to fix the camera in the reverse side - Ref: ADT_Scuv3_1
- Scuv3 option: Adaptor to fix the Scuv3 in the center dual screen - Ref: ADT_Scuv3_2
- Universal codec holder installed behind the screen - Réf : Scuv12



🇫🇷 Designed & Manufactured in France

REFERENCES

- EKINOX DE (Dual Screen) 40/46
- EKINOX DE (Dual Screen) 50/55
- EKINOX DE (Dual Screen) 60/65 Led